



主要零部件	阀体、阀盖、闸板	WCB	ZG1Cr18Ni9Ti	ZG1Cr18Ni12Mo2Ti	ZG2Cr5Mo
	阀杆	1Cr13	1Cr18Ni9Ti	0Cr18Ni12Mo2Ti	20Cr1Mo1V1
	阀杆螺母	ZguAL10Fe3/球墨铸铁			
	填料	柔性石墨、石墨石棉盘根			
主要参数	适用介质	蒸汽、油品、水等	硝酸类	醋酸类	蒸汽、油品、水等
	适用温度℃	≤425	≤200	≤200	≤425

型号	公称		主要结构尺寸(mm)				阀体材料	性能规范		备注
	通径DN(mm)	压力PN(MPa)	D	L	H	电动装置型号		适用温度℃	适用介质	
Z43D(F)-16C	50	1.6	160	200	178		WCB	常温	石油、天然气等	电动装置型号供Z943选用
	65	"	180	200	190		"	"		
KZ43D(F)-16C	80	"	195	250	203		"	"		
	100	"	215	250	229		"	"		
KZ543D(F)-16C	150	"	280	300	267	Z20-18/80	"	"		
	200	"	335	350	292	Z20-18/80	"	"		
KZ643D(F)-16C	250	"	405	400	330	Z30-18/80	"	"		
	300	"	460	450	356	Z45-18/80	"	"		
KZ943D(F)-16C	350	"	520	500	381	Z60-18/80	"	"		
	400	"	580	550	406	Z90-18/80	"	"		
	450	"	640	550	432		"	"		
	500	"	705	600	457	Z120-18/80	"	"		

	600	"	840	650	508	Z180-18/80	"	"		
	700	"	910	700	610	Z250-18/80	"	"		
Z43D-25	50	2.5	160	200	216		WCB	常温	石油、天然气等	电动装置型号供Z943选用
	65	"	180	200	241		"	"		
KZ43D-25	80	"	195	250	283		"	"		
	100	"	230	250	305		"	"		
KZ543D-25	150	"	300	300	403	Z20-18/80	"	"		
	200	"	360	350	419	Z30-18/80	"	"		
KZ643D-25	250	"	425	400	457	Z45-18/80	"	"		
	300	"	485	450	502	Z60-18/80	"	"		
KZ943D-25	350	"	550	500	762	Z90-18/80	"	"		
	400	"	610	550	838	Z120-18/80	"	"		
	450	"	660	550	914	Z180-18/80	"	"		
	500	"	730	600	991	Z180-18/80	"	"		
	600	"	840	650	1143	Z250-18/80	"	"		
Z43D(H)-40	50	4	160	250	216		WCB	常温	石油、天然气等	电动装置型号供Z943选用
	65	"	185	250	241		"	"		
KZ43D(H)-40	80	"	195	300	283		"	"		
	100	"	230	300	305		"	"		
KZ543D(H)-40	150	"	300	350	403	Z30-18/80	"	"		
	200	"	375	400	419	Z30-18/80	"	"		
KZ643D(H)-40	250	"	445	450	457	Z45-18/80	"	"		
	300	"	510	500	502	Z60-18/80	"	"		
KZ943D(H)-40	350	"	570	550	762	Z90-18/80	"	"		
	400	"	655	600	838	Z180-18/80	"	"		
	450	"	680	600	914	Z180-18/80	"	"		
	500	"	755	680	991	Z250-18/80	"	"		
	600	"	890	740	1143	Z350-18/80	"	"		
Z43D(H)-64	50	6.4	175	300	292		WCB	常温	石油、天然气等	电动装置型号供Z943选用
	65	"	200	300	330		"	"		
KZ43D(H)-64	80	"	210	350	356		"	"		
	100	"	250	350	432		"	"		
Z543D(H)-64	150	"	340	400	559	Z30-18/80	"	"		
	200	"	405	450	660	Z45-18/80	"	"		
Z643D(H)-64	250	"	470	500	787	Z90-18/80	"	"		
	300	"	530	550	838	Z120-18/80	"	"		
Z943D(H)-64	350	"	595	550	838	Z180-18/80	"	"		
	400	"	670	600	991	Z250-18/80	"	"		
	450	"		600	1092	Z250-18/80	"	"		
	500	"	800	680	1194	Z350-18/80	"	"		
	600	"	930	740	1397		"	"		
Z43H-100	50	10	195	300	292		WCB	常温	石油、天然气等	电动装置型号供Z943选用
	65	"	220	300	330		"	"		
KZ43H-100	80	"	230	350	356		"	"		
	100	"	265	350	432		"	"		
Z543H-100	150	"	350	400	559	Z60-18/80	"	"		
	200	"	430	450	660	Z90-18/80	"	"		
Z643H-100	250	"	500	500	787	Z120-18/80	"	"		
	300	"	585	550	838	Z180-18/80	"	"		
Z943H-100	350	"	665	600	889	Z250-18/80	"	"		
	400	"	715	680	991	Z350-18/80	"	"		